

Powerslide HC Evo, 165mm Mounting

(Design might vary)

¹ Measurement without Head!

² Measurement of Complete Axle



908052, black
Time Buckle
940381, gunmetal
Fixation Screw M4, L = 6mm¹

908054, black
Cuff Screw fitting FSK II Cuff
Ø 18mm, L = 13mm¹, M6

900594/l/r, black
Universal Flap II left & right
940383, gunmetal
Fixation Screw M4, L = 9mm¹

Spider Pro (rockered) Alu Frame
- 219mm / 4x 72mm
- 231mm / 4x 76mm
- 243mm / 4x 80mm
- 165mm Mounting
- Mounting Screw
M6, L = 13,5mm¹

Optional
908051/1
Urban Brake Size S (max. 4x
80mm)
900021, black
Brakepad

940377, black
Strap
36-41 = 19cm
42-46 = 21cm
940381, gunmetal
Fixation Screw
M4, L = 6mm¹ (top)
940383, gunmetal
Fixation screw
M4, L = 9mm¹ (bottom)

940411/155, black
Waxed Laces, 155cm

940390, black
Velcro Strap
36-39 = 14,5cm
40-43 = 15,5cm
44-46 = 16,5cm

Wheels
max. 72mm (36-39)
max. 76mm (40-41)
max. 80mm (42-46)
Bearings
608 Standard
Spacer
Ø 8mm, L = 10,25mm

940371, silver
Single Axle
Ø 8mm, L = 34mm², M7

908053/l/r, black
Side Protector left/right
incl. Hardware